

Ecoglo S20 Exit Signs FAQs

Q *How much do they cost?*

A Most commonly less than \$60+GST trade price, but signs that need to be seen from more than 16 metres cost more, and if standard brackets are required to mount the signs from a ceiling, or to protrude from a wall, the cost is an extra \$10 - \$20 depending on the size required. Ecoglo also offer a range of architectural brackets to complement any environment - please visit our website www.ecoglo.co.nz, or contact info@ecoglo.com for more information and pricing.

Q *Do they need an electrical light installed near them?*

A No, they are designed to make use of the existing light in the building.

Q *How long do they last?*

A A minimum of 30 years when installed indoors before there would be any measurable change in performance, and a minimum of 15 years outdoors for outdoor coated signs¹.

Q *What maintenance is required?*

A Make sure they are cleaned of dust or dirt build up. If the building doesn't need any other emergency lighting, in many cases Ecoglo S20 exit signs will not need to be part of the annual building WOF schedule.

Q *F8/AS1 requires that they be illuminated with a minimum of 100 lux to make sure they are charged ready for an emergency.*

What if there isn't 100 lux where the sign needs to be?

A Ecoglo S20 exit signs are designed to work in most normal lighting situations. Ecoglo's professional engineer can design an alternative solution to meet F8 in situations where there is as little as 55 lux available. This is a free service. Contact Ecoglo (engineer@ecoglo.com) for details.

Q *Can LED lighting be used for charging Ecoglo S20 exit signs?*

A Yes, any lighting, including LEDs, with a colour temperature of 4000K or more, is suitable for charging Ecoglo S20 exit signs. 4000K or more is typical for schools, offices, commercial and industrial lighting, and most retail stores

Q *Do the lights near the exit signs need to be turned on before the building is occupied?*

A No. Ecoglo S20 exit signs have been independently tested to confirm they meet the F8/AS1 luminance (brightness) requirement for Risk Group C buildings¹ after, at most, 5 minutes charging at 100 lux.

Q *What happens if there is a lights-out emergency in the first 5 minutes of occupation?*

A In most cases a sign will have sufficient residual charge from when there was light on it before, but even if the sign has become fully discharged and someone enters a dark space and turns on a light, the signs will meet the F8/AS1 brightness requirement for a longer

evacuation time than the time since the light was turned on. By the time 5 minutes has elapsed the signs will have the full 30 minutes charge required for Risk Group C buildings².

Q *How reliable are they?*

A They have no moving parts or components that will need replacing. As long as they are installed where there are normal indoor light levels, and they are kept reasonably clean, and not physically damaged, they will be visible in an emergency for the time required by F8 and F6 for at least 30 years.

Q *Where are they made?*

A They are designed and manufactured in Christchurch, using a unique process that was developed locally, over twenty years ago.

Q *Where can they be used?*

A Ideal places are in building spaces that are normally occupied when the signs may need to be used, such as classrooms, offices, meeting rooms, retail spaces, factories, and warehouses. In these places if the space becomes dark, the occupier will turn on a light, making sure that the signs remain well charged. Ecoglo S20 exit signs can also be used in spaces that aren't normally occupied (such as corridors linking rooms and stairwells), but there needs to be a management process for making sure that the signs are always sufficiently charged when someone may need to use them. Contact Ecoglo for more details.

Q *Who can install them?*

A Anyone who knows how to put a screw into a wall, and knows where the exit signs need to be installed to meet F8.

Q *What are their environmental credentials?*

A They are made in New Zealand in a factory that uses electricity (from a supplier committed to sustainable electricity production) as its only energy source. The factory creates no commercial liquid effluent, and negligible air emissions. The signs have no replaceable parts which would need to be disposed of, and no cadmium or mercury. They normally don't require any electricity to be used to keep them charged. They have an extremely long life, and if for any reason they need to be disposed of, they can be included with other aluminium products for aluminium recycling.

Q *Can they be used outdoors?*

A Yes, they are designed to meet the rigours of long term outdoor exposure in our harsh Southern Hemisphere environment. No matter what the weather, they can meet the requirements of F8 for several hours after sunset, or 24/7 when the distance they need to be seen from is no more than half their rated viewing distance. Contact Ecoglo for specific details.

Q *Do Ecoglo photoluminescent exit signs meet AS 2293?*

A In 2017 Standards Australia decided that AS 2293 does not cover photoluminescent exit signs, only internally and externally illuminated exit signs. More importantly, Ecoglo photoluminescent exit signs do meet NZBC F8/AS1.

¹ Signs specially coated for outdoor conditions

² Almost all buildings with less than 1000 occupants are Risk Group C